




Floor luminaire with direct light for outdoor use.	Light as a tool for guiding people along pathways or for creating depth.	The stem is in AISI 316L stainless steel. The spotlight is in textured matt black painted aluminium and is adjustable in all directions. Each pole can host one or two spotlights. An additional spotlight can be purchased separately. It is fixed to the ground with a textured matt black painted aluminium flange. An anchoring bolt accessory is available for lawns.	The light source is LED with integrated module. The electric cable is matt black and 7 m long. The driver is not included but is available as an accessory. An electric connector is included for outdoor use.
Apparecchio di illuminazione da terra, a luce diretta, per esterni.	La luce come strumento per condurre le persone lungo i percorsi o creare profondità.	Lo stelo è in AISI 316L. Il proiettore è in alluminio verniciato nero opaco texturizzato ed è orientabile in tutte le direzioni. Ogni palo può ospitare fino a due proiettori. Un proiettore addizionale può essere acquistato separatamente. Il fissaggio al suolo avviene mediante una flangia in alluminio verniciato nero opaco texturizzato. È disponibile l'accessorio tirafondo per i terreni erbosi.	La sorgente luminosa è a LED e a modulo integrato. Il cavo elettrico è di colore nero opaco e 7 m di lunghezza. Il driver non è incluso, ma è disponibile come accessorio. È incluso un connettore elettrico per esterni.

Finish	.00	Standard
		Custom finish available on request (LED head only). Finitura personalizzata su richiesta (solo per testa LED).




BUBKA

8,4W
Max 700mA DC
2700K - 639lm / 3000K - 639lm
CRI >90
Driver not included
CE IP65

Standard - 2700K	1A3600000.27.20
Standard - 3000K	1A3600000.30.20

Compulsory accessories / Accessori obbligatori

Drivers / Alimentatori




Driver / Alimentatore		Not included
220-240V(100-127V)	700mA/30W(15W)/IP68/ON/OFF	1Z0241110

Optional accessories / Accessori opzionali

Installation kits / Kit d'installazione




Driver connector IP68 / Connettore driver IP68		Included
	1 Piece	1A1660000.00.00



Anchoring bolt / Tirafondo		Not included
Cut-out Ø 250 mm Minimum space for mounting 350 mm		1A3620000.00.00

Lighting modules / Corpi illuminanti



Additional LED head / Testa LED supplementare		Not included
Matt Black	Max 700mA DC - 8,4W 3000K - 639lm - CRI >90	1A3610400.30.20
	Max 700mA DC - 8,4W 2700K - 639lm - CRI >90	1A3610400.27.20

